

ANTI-STATIC STEAM HOSE

250 PSI / 17 BAR

MADE IN ITALY



TECHNOFLEX - ITALY ANTI-STATIC STEAM HOSE W. P. 250PSI/17 BAR

TechnoFlex Steam Hose - 250 PSI / 17 BAR

A highly flexible, heat-resistant hose designed for steam applications in demanding industrial environments, including refineries, shipyards, chemical plants, steel mills, and foundries. Engineered to withstand high temperatures up to 210°C and a constant pressure of 250 PSI, it features uniform thickness for enhanced durability and reliability. Its robust construction ensures long-lasting performance, making it a dependable choice for heavy-duty industries requiring efficient and safe steam transfer.

- **Temperature Range:**
 - Service temperature upto +210°C (+410°F)
- **Reinforcement:**
 - Double braid of high-tensile steel wire.
- **Tube:**
 - Heat resistant EPDM rubber compound.
- **Cover:**
 - Heat resistant EPDM rubber compound resistant to heat, ozone & a geing.
- **Applicable STD :**
 - IS 10655 TYPE III ,BS 5342 TYPE 2 , ISO 6134
- **Standard Length:**
 - 40m /60m
- **Safety Factor:**
 - 10:1

HOSE I.D.		HOSE O.D.		WORKING PRESSURE		BURST PRESSUER		WEIGHT
mm	inch	mm	inch	bar	psi	bar	psi	Kg/m
13	1/2 "	25	1 "	17	247	170	2465	0,530
16	5/8 "	28	1-7/64 "	17	247	170	2465	0,600
19	3/4 "	32	1-1/4 "	17	247	170	2465	0,750
25	1 "	38	1-1/2 "	17	247	170	2465	0,950
32	1-1/4 "	46	1-12/16 "	17	247	170	2465	1,300
38	1-1/2 "	52	2-3/64 "	17	247	170	2465	1,580
51	2 "	68	2-11/16 "	17	247	170	2465	2,300
63.5	2-1 "	79.5	3-1/8 "	17	247	170	2465	3,300
76.2	3 "	93	3-21/32 "	17	247	170	2465	5,500
101.6	4 "	124	4-7/8 "	17	247	170	2465	7,500

Authorized Distributor:
MOHAMMED AHMED AL-AWANI TRADING COMPANY

Dewatering Pump Sales | Dewatering Accessories | Hoses & Fittings | Pump Parts | Pump Rental | Pump Service

